



CUSHMAN®

HAULER® 800



PRACTICALITY MEETS VERSATILITY.

The Cushman® Hauler 800 is built to transport people, tools and equipment around any facility or golf course with ease. Powered by your choice of a reliable 48-volt AC electric drivetrain or fuel-efficient 13.5 hp gas engine, the Hauler 800 is conveniently equipped to perform a variety of duties. When versatility and efficiency are a priority, the Hauler 800 has a proven track record that can't be beat.

LET'S WORK.®

13.5 HP
EFI GAS

8.4 CU FT
CARGO BED

900 LB
TOW CAPACITY

48V AC
ELECTRIC
DRIVETRAIN



CUSHMAN® HAULER® 800



OPTIONS & ACCESSORIES

- Improved Surface Tires*
- Brake Lights
- Taillights
- Fuel/Oil Gauge (gas vehicle only)
- On-board Charger (electric vehicle only)
- Premium Steering Wheel
- 2" Rear Receiver Hitch
- LED Headlights with High/Low Beam
- ROPS-Certified Cab
- Bed Dividers
- Long-Handled Tool Holder
- Cargo Mesh Netting
- Weather Enclosure
- USB Outlet
- 12-Volt Outlet
- Canopy Storage Net
- Rearview Mirror
- Side body color

	ELECTRIC MODEL	EFI GAS MODEL
BODY & CHASSIS		
FRAME	Welded Steel w/ E-Shield e-coat plus DuraShield™ Powder Coat	
BODY & FINISH	Injection Molded TPO (Front) /Injection Molded PP (Rear)	
STANDARD COLOR	Patriot Blue, Forest Green	
DIMENSIONS		
OVERALL LENGTH	110 in (279.4 cm)	
OVERALL WIDTH	49 in (125 cm)	
OVERALL HEIGHT	47 in (119.4 cm) (No Canopy) 69.5 in (176.5 cm) (w/ Struts & Roof)	
WHEEL BASE	65.5 in (166.4 cm)	
WHEEL TRACK	37 in (94 cm) Front / 38 in (96.5 cm) Rear	
GROUND CLEARANCE	4.3 in (10.9 cm)	
CARGO DECK CAPACITY	8.4 cu ft (0.24 m³)	
CARGO DECK DIMENSIONS	44.5 in x 28.5 in x 12 in (113 cm x 72 cm x 30.5 cm)	
CARGO DECK MATERIAL	Roto-Molded Polyethylene	
POWER		
POWER TRAIN	48V AC	4-Cycle, 24.5 ci (401cc)
VALVE TRAIN	N/A	Single Cylinder OHV
HORSEPOWER (KW)	4.4 HP (3.3 kW) Continuous	13.5 hp (10.1 kW)
ELECTRICAL SYSTEM	48V	Starter/Generator. Solid State Reg.
BATTERY (QTY/TYPE)	Six, 8V Deep Cycle	One, 12V Maintenance Free
BATTERY CHARGER	48V DC PowerWise™ QE, 120V AC, UL/CSA	N/A
KEY OR PEDAL START	Pedal	
AIR CLEANER	N/A	Replacable Dry Cartridge
LUBRICATION	N/A	Pressurized Oil System
OIL FILTER	N/A	Spin-On
COOLING SYSTEM	N/A	Air Cooled
FUEL CAPACITY	N/A	5.96 Gallon (22.6 L) tank
SPEED CONTROLLER	235 Amp AC Controller	N/A
DRIVE TRAIN	Motor Shaft Direct Drive	Continuously Variable Transmission
TRANSAXLE	Differential w/ Helical Gears	
GEAR SELECTION	Dash-Mounted Forward-Neutral-Reverse	Forward - Reverse
REAR AXLE RATIO	16.99: 1	11.47: 1 (Forward) 14.35:1 (Reverse)
PERFORMANCE		
SEATING CAPACITY	2-Person (Bench)	
WEIGHT W/O BATTERIES	735 lb (333.4 kg)	761 lb (345.2 kg)
CURB WEIGHT	1101 lb (499.4 kg)	791 lb (358.8 kg)
VEHICLE LOAD CAPACITY	800 lb (362.9 kg)	
BED LOAD CAPACITY	400 lb (181.4 kg)	
TOWING CAPACITY	900 lb (408.2 kg)	
OUTSIDE CLEARANCE CIRCLE	18.9 ft (5.8 m)	
SPEED	14.5 mph ± 0.5 mph (23.3 kph ± 0.8 kph)	
STEERING & SUSPENSION		
STEERING	Self-Compensating Rack & Pinion	
SUSPENSION	Leaf Springs w/ Hydraulic Shock Absorbers	
SERVICE BRAKE	Rear Wheel Mechanical, Self-Adjusting Drum	
PARKING BRAKE	Self-Compensating, Single-Point Engagement	
TIRES (FRONT & REAR)	18 x 8.5- 8 (6 Ply-rated)	

www.cushman.com

©2019 Textron Specialized Vehicles Inc. Features and specifications of the vehicles are subject to change without notice. Vehicle as photographed may include options not included on base model.

82288-G8 (Rev. 11/2019)