



CUSHMAN®

SHUTTLE™ 8



EFFICIENT AND PRODUCTIVE HIGH VOLUME TRANSPORTATION.

The Cushman® Shuttle™ 8 is perfect for transporting large groups of people throughout any facility. With six forward-facing seats and two rear-facing seats, the Shuttle 8 can move up to eight people with ease. Choose between an energy-efficient 72V AC electric drivetrain or powerful 13.5 hp EFI gas engine. Features like a large canopy, ergonomically-designed seating, and dependable performance keep guests and workers happy.

LET'S WORK.®

**13.5HP
EFI GAS**

**72V
AC ELECTRIC
DRIVETRAIN**

**8
PERSON
SEATING
CAPACITY**



CUSHMAN® SHUTTLE™ 8



HEADLIGHTS



BENCH SEATING

RACK-AND-PINION
STEERING

OPTIONS & ACCESSORIES

- Rearview Mirror
- Windshield
- Canopy
- Hour Meter
- Individual Key Switch
- Pinstripes
- On Board Charger
- Body Color (Forest Green, White, Ivory, Black or Custom Options)
- Turn Signal with Four-Way Flashers
- Brakelights
- LED Headlights
- CE Kit (gas only)

ELECTRIC MODEL

EFI GAS MODEL

BODY & CHASSIS	
FRAME	Welded Steel w/ DuraShield™ Powder Coat
BODY & FINISH	Injection Molded TPO
STANDARD COLOR	Patriot Blue
DIMENSIONS	
OVERALL LENGTH	167.5 in (425 cm)
OVERALL WIDTH	49.5 in (126 cm)
OVERALL HEIGHT	45.5 in (116 cm) (w/o Roof) / 76.0 in (193 cm) (w/ Struts & Roof)
WHEEL BASE	123.4 in (313 cm)
WHEEL TRACK	36.0 in (91 cm) Front / 38.0 in (97 cm) Rear
GROUND CLEARANCE	3.0 in (8 cm)
CARGO DECK CAPACITY	400 lb (181 kg)
POWER	
POWER SOURCE	72V AC
VALVE TRAIN	N/A
HORSEPOWER (KW)	22.4 hp (16.7 kW) Intermittent
ELECTRICAL SYSTEM	72V
BATTERY (QTY/TYPE)	Six, 12 Volt Deep Cycle
BATTERY CHARGER	1000 Watt, 72V, 120/230V VAC UL Listed
KEY OR PEDAL START	Pedal
AIR CLEANER	N/A
LUBRICATION	N/A
OIL FILTER	N/A
COOLING SYSTEM	N/A
FUEL CAPACITY	N/A
SPEED CONTROLLER	350 Amp AC
DRIVE TRAIN	Motor Shaft Direct Drive
TRANSAXLE	Differential w/ Helical Gears
GEAR SELECTION	Dash-Mounted Forward-Neutral-Reverse
REAR AXLE RATIO	17:1
PERFORMANCE	
SEATING CAPACITY	8-Person
WEIGHT W/O BATTERIES	1203 lb (546 kg)
CURB WEIGHT	1695 lb (769 kg)
VEHICLE LOAD CAPACITY	1600 lb (726 kg)
BED LOAD CAPACITY	400 lb (181 kg)
OUTSIDE CLEARANCE CIRCLE	33 ft (10 m)
SPEED	16.5 mph ± 0.5 mph (26.4 kph ± 0.8 kph) (High Speed) 12 mph ± 0.5 mph (19.3 kph ± 0.8 kph) (Low Speed)
STEERING & SUSPENSION	
STEERING	Self-Compensating Rack & Pinion
SUSPENSION	Leaf Springs w/ Hydraulic Shock Absorbers
SERVICE BRAKE	4-Wheel Hydraulic Brakes Front Disk, Rear Drum
PARKING BRAKE	Self-Compensating, Single-Point Engagement
TIRES (FRONT & REAR)	215/60-8

www.cushman.com

©2020 Textron Specialized Vehicles Inc.
Features and specifications of the vehicles are subject to change without notice.
Vehicle as photographed may include options not included on base model.

82305-G6 (Rev. 08/2020)