GO-4 XTF GAS - SPECIFICATIONS

MOTOR

66 h.p., liquid cooled, 3-cylinder, overhead cam, 4-cycle, electronically fuel injected, ultra efficient 1.0L with EGR clean burning emissions control.

TRANSMISSION

4-speed automatic

(automotive transaxle with electronically controlled shift)

DIMENSIONS

72" Overall Height with Cab 140" Overall Length 55" Overall Width 22 Foot Outside Turning Diameter 11 Foot Turning Radius 95" Wheelbase

BRAKING

Hydraulic Disc Brakes on all Three Wheels
With Dual Master Cylinder
Parking – Hydraulic over Mechanical

ELECTRICAL SYSTEM

Charging – Heavy Duty automotive alternator
DOT approved LED headlights
DOT Approved LED Stop / Tail and Turn Lights
DOT Approved High Visibility Stop Light
Starting – 12-volt starting motor.
Interlock prevents starter from operating
unless shift lever is in park or neutral.

Gauges - LCD Digital Display

Speed, Odometer, Hour Meter, Warning Message,

Fuel Level, Oil pressure warning,

three stage water temperature light

(blue / still cold, red/ running too hot,

off / normal temp)

Wiring – Pre Wired for Radio and Municipal

Lighting(Option)

SPEED

Electronically Limited to a Maximum of 40mph (45mph optional)

COLOR

White Body Panels and Black Chassis

FUEL TANK AND MILEAGE

9 US Gallon Tank, up to 40-45 MPG (based on factory testing and CARB testing, excludes constant idle time)

SUSPENSION

Front – Leading Link Suspension Polyurethane Isolation System Rear – Independent McPherson Strut

CLIMATE CONTROL

Liquid Core 20000 BTU Heater(Option)
Air Conditioning (Option)

STEERING

Adjustable Tilt Steering Wheel with Center Mounted Horn

TIRES

165/60 14" Low-Rolling Resistance All Season Radial with Steel Rim

STRUCTURE

3-Wheel Platform with Ultra Tough Heavy Duty
2.5"Rollbar Chassis
White Aluminum and Plastic Body Panels

White Aluminum and Plastic Body Panels Aluminum Rear Deck with Optional Clamping Walls Hinged Door (Option), Steel Front and Rear bumpers, Optional Exterior Nerf Bars

FEATURES

Two Outside Rear View Mirror
Inside Rear View Mirror (Full length Option)
Rear View Back Up Camera(Option)
Electric Windshield Wiper with Intermitted Control
And Windshield Washer
Inside Cab Ceiling Light(Option)
Floor Mat
12 V DC Accessory Port
LTA (Lateral thrust alarm)

SEAT

One Passenger Adjustable Forwards/Backwards,
Recline, Leatherette material
3 Point Shoulder Harness Seat Belts

WEIGHT CAPACITY

Vehicle Weight – 1600 Pounds – Base w/o Options Rated Total Payload Capacity, 650lbs w/ Operator

WARRANTY

One Year Full Warranty on Manufacture Defects
Technician Travel Time Excluded

OPTIONS

Please Inquire for Full Listing

Published March 2020 by Westward Industries Ltd — Specifications are subject to change — Please check with Westward before finalizing any Bids — These vehicles comply with US DOT vehicle safety standards, EPA and CARB standards, for Motorcycles. In some states we may comply with Autocycle regulations.