GO-4 XTR GAS REFUSE - SPECIFICATIONS

SUSPENSION

Front – Leading Link Suspension **Polyurethane Isolation System** Rear - Independent McPherson Strut with fortified bracketry for higher payload **CLIMATE CONTROL** Liquid Core 20000 BTU Heater(Option) Air Conditioning (Option) STEERING Adjustable Tilt Steering Wheel with Center Mounted Horn TIRES 165/60 14" All season Radial on front, Rear 2-13 or 14" High load index Tires w Steel Rim(Check for details) STRUCTURE 3-Wheel Platform with Ultra Tough Heavy Duty 2.5" Rollbar Chassis White Aluminum and Plastic Body Panels 1.75 Cub YD Heavy Duty Poly Bin with Fortified Steel Structure and Hydraulic Pump Hinged Door (Option), Steel Front and Rear bumpers, Exterior Nerf Bars(Option - if no doors added, front nerf is required) FEATURES Two Outside Rear View Mirror Rear View Back Up Camera Electric Windshield Wiper with Intermitted Control And Windshield Washer Inside Cab Ceiling Light(Option) Floor Mat 12 V DC Accessory Port LTA (Lateral thrust alarm) SEAT One Passenger Adjustable Forwards/Backwards, Recline, Leatherette material **3** Point Shoulder Harness Seat Belts WEIGHT CAPACITY Vehicle Weight with Bin- 1900 Pounds -Base, no Option Rated Total Payload Capacity, 1000lbs w/ Operator WARRANTY One Year Full Warranty on Manufacture Defects Technician Travel Time Excluded **OPTIONS** Please Inquire for Full Listing

MOTOR

66 h.p., liquid cooled, 3-cylinder, overhead cam, 4-cycle, electronically fuel injected, ultra efficient 1.0L with EGR clean burning emissions control. TRANSMISSION 4-speed automatic (automotive transaxle with electronically controlled shift) DIMENSIONS 72" Overall Height with Cab 147" Overall Length 57" Overall Width 22 Foot Outside Turning Diameter **11 Foot Turning Radius** 95" Wheelbase BRAKING Hydraulic Disc Brakes on all Three Wheels With Dual Master Cylinder Parking – Hydraulic over Mechanical **ELECTRICAL SYSTEM** Charging – Heavy Duty automotive alternator DOT approved LED headlights DOT Approved LED Stop / Tail and Turn Lights DOT Approved High Visibility Stop Light Starting – 12-volt starting motor. Interlock prevents starter from operating unless shift lever is in park or neutral. Gauges – LCD Digital Display Speed, Odometer, Hour Meter, Warning Message, Fuel Level, Oil pressure warning, three stage water temperature light (blue / still cold, red/ running too hot, off / normal temp) Wiring – Pre Wired for Radio and Municipal Lighting(Option) SPEED Electronically Limited to a Maximum of 30 mph COLOR White Body Panels and Black Chassis FUEL TANK AND MILEAGE 9 US Gallon Tank, up to 40-45 MPG (based on factory testing and CARB testing, excludes constant idle time and high payloads)

Published March 2020 by Westward Industries Ltd – Specifications are subject to change – Please check with Westward before finalizing any Bids – These vehicles comply with US DOT vehicle safety standards, EPA and CARB standards, for Motorcycles. In some states we may comply with Autocycle regulations.