



HIGH PERFORMANCE SNOW & ICE EQUIPMENT

REINVENTED EVERY DAY.

CONTENTS

- Reinvented Every Day.....1-2
- Blaster™.....3
- BL™ 240/400/750.....4
- Mate™.....5
- Crossfire™.....6
- Polyhawk™.....7
- PV.....8
- MDV.....9
- UTG/RTG.....10
- Specialty..... 11-12
- Anti-Icers.....13
- Specifications.....14-22

We're proud to say we invented the first automotive snow plow.



REINVENTED EVERY DAY.

Today, Meyer offers the largest selection of spreaders in the industry, from small walk behinds to large municipal spreaders. If a vehicle is used for work, chances are we have a spreader for it.



But we're even more proud to say that spirit of invention and innovation lives on today. It's our culture to constantly search for ideas and new ways to make snow and ice management easier and more efficient with features like pre-wetting and America's best warranty. Because you're never satisfied until the job is done right, and neither are we.

The 1930s



Developed the T-1 Electric Hydraulic Lift, the first ever.

The 1940s



Designed the first plow for 4-wheel drive vehicles.

The 1970s



In 1972 the Meyer "Mini Spreader" was introduced. The perfect size to control ice where the big trucks couldn't.

The 1990s



In 1999 black thermoplastic replaced fiberglass on the hopper.



Meyer spreaders help control your cost and the impact of ice-melt on the environment by spreading the right amount of material when and where you need it.

Some spreader models shown with optional equipment.



Patented brush auger stops salt leakage.



BLASTER™

STEADY-FLOWING PREMIUM SPREADER CONTROLS THE FLOW OF ANY MATERIAL

Spreading a wide variety of material requires spreaders to have different performance characteristics. That's why the Meyer Blaster gives you the ability to customize the configuration. From auger options to vibrator kits, you can create the ultimate spreading machine.

All Blasters (except "S" models) come standard with a patented coarse material brush auger to prevent rock salt from leaking out of the hopper throat.



SEE PAGE 14 FOR DETAILED SPECIFICATIONS

QUICK FACTS

- VEHICLES: Light to 1-ton Pick-ups, Tractors with 3-point Hitch Receiver Hitch
- TYPE: Receiver Hitch
- CAPACITY: 6.5 cu. ft. (350 lbs.); 12.8 cu. ft. (750 lbs.)
- MATERIALS: Salt or Calcium Chloride
- CONSTRUCTION: Polyethylene

One-touch auto control

One-touch operation provides total control over Blaster spreaders. The illuminated in-cab controller (patent pending) includes an on/off switch, blast mode which provides an on-command 70 amp surge, and a vibrate mode. Regulate the spinner speed with the variable speed controller. Spinner stops automatically when the brake is applied.



Toughest motor available

Blaster's 1/2 HP motor is the most powerful motor available today. The direct-drive system links the motor directly to the auger, creating up to 75% more auger power to easily grind through large chunks of material and provide an even material spread pattern.



BLASTER™

www.meyerproducts.com



Patented brush auger stops salt leakage.

BL-750 is new for 2015.

BL 240/400/750™

ECONOMICAL ICE CONTROL FOR PROPERTY MANAGERS AND CONTRACTORS

Meyer Base Line tailgate spreaders attach using a 2" receiver hitch and are perfect for small to medium-sized jobs like long driveways and small lots.



All BL 240/400/750 models come standard with a patented coarse material brush auger to prevent rock salt from leaking out of the hopper throat.

SEE PAGE 15 FOR DETAILED SPECIFICATIONS

QUICK FACTS

VEHICLES: Light/Full-Sized Trucks, SUVs, Tractors and Utility Vehicles
TYPE: Receiver Hitch
CAPACITY: 3.7 cu. ft. (240 lbs.); 6.3 cu. ft. (400 lbs.); 10.5 cu. ft. (750 lbs.)
MATERIALS: Bagged Rock Salt
CONSTRUCTION: Polyurethane Hopper, Carbon Steel Frame

In-cab controller

Intuitive and reliable variable speed touch pad controller with easy-to-use fast, slow and vibrate buttons delivers a precise spread pattern up to 25 feet.



Direct-drive motor

The BL-240/400/750's direct-drive system links the 1/6 HP motor directly to the auger, creating up to 75% more auger power than non-direct drive set-ups. The motor provides superior clump-busting performance. Its marine-style electrical plug keeps the water out to ensure consistent electrical flow from the vehicle's battery.



Meyer Blaster/BL Spreader Augers Help Keep Material Moving.

You should always use dry free-flowing material for optimal spreading performance. But if your material tends to get sticky, use the chart below to find the right extensions for your application needs.

Auger Part #	Description	Standard On...	Can Be Used With...	You Should Use This...
34302	Rock Salt Brush Auger (Coarse Material)	BL 240 BL 400 BL 750 Blaster 350 Blaster 750R	BL 240 BL 400 BL 750 Blaster 350 Blaster 350S* Blaster 750R Blaster 750RS*	...to reduce coarse material like rock salt from leaking out of the hopper when the spinner is idle
34303	Fine Salt Brush Auger (Fine Materials)	Sold as an accessory only	BL 240 BL 400 BL 750 Blaster 350 Blaster 350S* Blaster 750R Blaster 750RS*	...to reduce fine material from leaking out of the hopper when the spinner is idle.
34306	Steel Spiral Auger	Blaster 350S Blaster 750RS	BL 240 BL 400 BL 750 Blaster 350S Blaster 750RS	...when applying material made up of different types of aggregate , (e.g., grit and cinders). The steel spiral auger must be used.
34118	Aggregate Auger Kit	Sold as an accessory only	BL 240 BL 400 BL 750 Blaster 350 Blaster 350S Blaster 750R Blaster 750RS	...to prevent coarse aggregate material (e.g., grit, cinders, gravel), from clogging in the discharge throat.
34604	Spiked Aggregate Extension Kit (attaches to 34306 or 34118)	Standard on Blaster "S" units.	Blaster 350S Blaster 750RS	...when you want to focus the agitation of aggregate material.
34109	Chained Aggregate Extension Kit (attaches to 34306 or 34118)	Sold as an accessory only	Blaster 350S Blaster 750RS	...when you want to agitate heavier aggregate like grit or gravel combinations.

* Auger extensions cannot be used with brush augers 34302 or 34303.

PRECAUTION:

All tailgate spreaders, regardless of brand, require the use of free-flowing material for optimum/best performance.

USING EXTENSIONS:

Aggregate auger extensions (34604 and 34109) work exclusively with auger 34306 or 34118 and are designed to provide added agitation to non-salt materials, e.g. materials such as grit, gravel, sludge, cinders, etc. These extensions are designed to be used in conjunction with the in-hopper baffle kit. Baffle kits come standard with the 750RS and 350S models. Other Blaster models will accept extensions but kit # 34600 is required. Auger extensions can not be used with Rock Salt.

MEET OUR MOVERS AND SHAKERS



“S” Series Blasters. A systematic way to create steady-flowing material.

Let's face it, any spreader is going to be able to dispense “dry, free-flowing material.” But the reality is, most material is dry and free flowing for only so long. That's why all Meyer “S” Series Blasters have been designed to systematically create a steady flow of material to the spinner.

“S” series come standard with an on-demand vibrator, a load-bearing baffle plate – that lessens the pressure on the auger – and a multi-spiked auger that reaches deep into the hopper. All of these features work together to break up coagulated material creating a constant flow of material to the spinner. This means you get reliable performance in less than perfect conditions.

See reverse side for options.



MATE™

THE ONLY STRAP-MOUNTED PICK-UP TRUCK SPREADER

The Mate comes fully assembled and attaches without tools or drilling. A swing-out option (*shown below*) is also available allowing the owner to access the bed of the truck from the tailgate. The Mate is perfect for parking lots and driveways.



SEE PAGE 15 FOR DETAILED SPECIFICATIONS

QUICK FACTS

VEHICLES:	3/4-ton + Pick-ups, Tractors with 3-point Hitch
TYPE:	Tailgate
CAPACITY:	9.0 cu. ft. (700 lbs.)
MATERIALS:	Salt, Fertilizer and Seed
CONSTRUCTION:	Polyethylene

One-touch auto control

One-touch operation provides total control over Mate spreaders. The illuminated in-cab controller (patent pending) includes an on/off switch, blast mode which provides an on-command 70 amp surge, and a vibrate mode. Regulate the spinner speed with the variable speed controller. Spinner stops automatically when the brake is applied.



Direct-drive motor

A commercial-duty 1/6 HP, 12V direct-drive motor drives the spinner directly off the motor drive shaft, providing energy-efficient power to the agitator system for optimum performance and reliability.



MATE™



Full-width hopper reduces material spillage into the vehicle bed to prevent corrosion.



CROSSFIRE™

FEATURING THE INDUSTRY'S ONLY INTEGRATED PRE-WET SYSTEM FOR PICK-UPS

Pre-wetting ice-melt material helps speed up the melting process and reduces how far the granules bounce when they hit the pavement. The end result, a safer surface using less material in less time. Available on deluxe models, integrated pre-wetting is just one of the many ways the Crossfire is better by design.



QUICK FACTS

VEHICLES:	3/4-ton and larger Pick-ups
TYPE:	Insert Hopper with Pre-wet included with Deluxe models
CAPACITY:	1.5 cu yds. (6 ft.); 2.0 cu. yds. (8 ft.)
MATERIALS:	Dry, Free-flowing Rock Salt
CONSTRUCTION:	Polyethylene



Built-in pre-wetting system

No hard-to-install tanks to add, and the system is fully plumbed with high-quality hoses and spray system. (DLX model only)



Integrated work light

Illuminates spread area and helps in maintenance operations. LED light included on DLX model, halogen light on standard model.

SEE PAGE 16 FOR DETAILED SPECIFICATIONS

REINVENTED EVERY DAY.



10 YEAR
WARRANTY *

POLYHAWK™

FEATURES A VIRTUALLY INDESTRUCTIBLE POLY HOPPER

Popular with contractors, the Polyhawk features an unprecedented 10-year warranty on the polyethylene hopper, the Polyhawk is perfect for spreading bulk materials like sand with rock salt.

SEE PAGE 16 FOR DETAILED SPECIFICATIONS

QUICK FACTS

- VEHICLES: 3/4 to 1-ton Pick-ups
- TYPE: Insert Hopper
- CAPACITY: 1.5 cu. yds. (6 ft.); 2.0 cu. yds. (8 ft.)
- MATERIALS: Salt, 50/50 Salt-Sand and Sand
- CONSTRUCTION: Polyethylene

Wireless controls

Our fully integrated wireless controller allows you to start and choke your engine as well as engage your drive system in a simple to use hand-held wireless controller. Electric Polyhawk models available with a hard-wired controller.



Spread material exactly where you need it

With Meyer's two internal and four external baffle adjustment systems, you're able to put down material in the right place, every time. Whether you want to spread four feet to the left, four feet to the right, or spread a thirty foot pattern, you can easily adjust the spreading pattern to meet your needs.



* 10 year warranty applies to poly hopper only.

POLYHAWK™

www.meyerproducts.com



PV

LETS YOU PLACE MATERIAL EXACTLY WHERE IT'S NEEDED

Meyer PV spreaders share many of the time-saving, long-lasting features of our larger MDV series spreaders, including two internal and four external baffle adjustment systems. Available with a 10.5 HP Briggs & Stratton engine, 11 HP Honda engine or electric drive, the choices are endless when removing snow and ice from roads and parking lots.

SEE PAGE 17 FOR DETAILED SPECIFICATIONS

QUICK FACTS

VEHICLES:	3/4-ton and larger Pick-ups
TYPE:	Insert Hopper
MATERIALS:	Salt, 50/50 Salt-Sand and Sand
CAPACITY:	Carbon Steel: 2.0 cu. yds. (8 ft.) Stainless Steel: 1.5 cu. yds. (6 ft.); 1.8 cu. yds. (7 ft.); 2.0 cu. yds. (8 ft.)



Inverted-V

Our inverted-V helps prevent material from bridging and slowing down the conveyor.

BL600

Meyer's most economical stainless steel insert hopper spreader.



REINVENTED EVERY DAY.



MDV

HIGHWAY-STYLE SPREADER FOR INCREASED MATERIAL CAPACITY

Meyer Medium Duty V-box (MDV) spreader features two internal and four external baffles, the MDV allows you to spread material exactly where it's needed on larger roads and parking lots.

SEE PAGE 18 FOR DETAILED SPECIFICATIONS

QUICK FACTS

VEHICLES:	Medium-duty (15,000 GVW and up)
TYPE:	Insert Hopper
CAPACITY:	3.5 cu. yds. (8 ft.); 4.0 cu. yds. (9 ft.); 4.5 cu. yds. (10 ft.)
MATERIALS:	Salt, 50/50 Salt-Sand and Sand
CONSTRUCTION:	Stainless Steel

Wireless controls

Our fully integrated wireless controller allows you to start and choke your engine as well as engage your drive system in a simple to use hand-held, wireless controller.



Spinner swings up and out of the way

No tools required, spinner easily swings up and out of the way for easy storing. When the spinner is in the up position, unload any material by running the conveyor.



UTG/RTG

CENTER DISCHARGE PERFORMANCE FOR DUMP TRUCKS

Meyer Under-Tailgate and Replaceable Tailgate spreaders use a combination of a self-contained auger with removable spinners. With or without central hydraulics, our electric tailgate models can easily be added to any dump truck so large roads and parking lots can be snow-free in no time.


SEE PAGE 19 FOR DETAILED SPECIFICATIONS

QUICK FACTS

VEHICLES:	Medium-duty Dump Trucks (15,000 GVW and up)
BODY WIDTH:	RTG: 78" - 84", RTG-XL: 84" - 90", UTG: 88" or 96"
MATERIALS:	Salt, 50/50 Salt-Sand
CONSTRUCTION:	Stainless Steel

Safety Interlock System

Our Safety Interlock System (electric or hydraulic) disables the auger when opening the bottom door making maintenance much safer and easier.



Center discharge for complete lane coverage

Whether you need a UTG or RTG, Meyer electric dump truck spreaders are perfect for parking lots because the center drop allows for complete lane coverage. It's only available from Meyer.

REINVENTED EVERY DAY.

HOTSHOT™

BROADCAST SPREADERS FOR YEAR-ROUND USE

Meyer Hotshots are compact, easy to maneuver and built to handle extreme conditions. Hotshots are the perfect solution for keeping walkways clear of snow and ice.

QUICK FACTS

TYPE:	Broadcast Spreader
CAPACITY:	0.9 cu. ft. (70 lbs.); 1.0 cu. ft. (85 lbs.); 1.25 cu. ft. (100 lbs.); 1.5 cu. ft. (120 lbs.)
MATERIALS:	Bagged Rock Salt, Free-flowing Granular Material
CONSTRUCTION:	Hopper - Polypropylene Frame - Carbon Steel or Stainless



Hotshot 100 HD

Hotshot 70 HD

Hotshot 70

Hotshot 120

Hotshot 85

SEE PAGE 20 FOR
DETAILED SPECIFICATIONS

HOTSHOT™

DROP SPREADERS FOR EXACT MATERIAL PLACEMENT

Meyer Hotshot Drop Spreaders are perfect for spreading material on walkways or pathways. Choose from a polyethylene 50 lb. capacity or a 100 lb. stainless steel capacity spreader to keep your walkways and pathways clear.

QUICK FACTS

TYPE:	Drop Spreader
CAPACITY:	0.8 cu. ft. (50 lbs.); 1.75 cu. ft. (100 lbs.)
MATERIALS:	Bagged Rock Salt, Free-flowing Granular Material
CONSTRUCTION:	Hopper - Polyethylene or Stainless Steel Frame - Metal with Powder Paint



Hotshot 100

Hotshot 50

SEE PAGE 20 FOR
DETAILED SPECIFICATIONS

SPECIALTY

BL-125

A TAILGATE SPREADER FOR ATVs

The BL-125 tailgate spreader is perfect for tight areas and walkways. It features an elevated heavy-duty electric motor built to withstand the harshest conditions. A fitted rubber cover seals the motor ensuring reliable performance. The BL-125 frame features corrosion resistant gloss black powder paint for years of reliable use.



Poly hopper

Standard with a built-in material agitator which spreads the flow of material evenly the first time



Impeller spinner shaft

Adjusts the spread pattern from 3' to 20'. This feature saves time and money because you are able to spread material exactly where you need it every time.

QUICK FACTS

TYPE:	Rear Rack Mount
CAPACITY:	125 lbs.
SPREAD WIDTH:	3 - 20 ft.
MATERIALS:	Salt, Calcium Chloride, Fertilizer and Seed
CONSTRUCTION:	Hopper - Polyethylene Frame - Metal with Powder Paint



SEE PAGE 21 FOR
DETAILED SPECIFICATIONS

CROSS CONVEYOR

TURN YOUR DUMP TRUCK INTO A WORKHORSE

Whether you are shouldering material, filling a ditch, patching asphalt or spreading sand*, this heavy-duty conveyor system saves you labor, time and material.



QUICK FACTS

VEHICLES:	Medium-duty Dump Trucks (15,000 GVW and up)
TYPE:	Dump Truck Tailgate
FLOW RATE:	240 tons/hr.
MATERIALS:	Asphalt, Granular Materials
CONSTRUCTION:	Carbon Steel



High temperature belt over chain

High temperature, belt-over chain conveyor makes dump truck functional during non-spreading activities.



Screw-type gate jacks

Allows material output adjustment when loaded.

SEE PAGE 21 FOR
DETAILED SPECIFICATIONS

* Requires optional spinner attachment. Not recommended for straight salt application.



ANTI-ICERS

FEATURES UNIQUE SPACE-SAVING TANK DESIGN

Meyer's anti-icer fits between the wheel wells of the vehicle and cab allowing you to utilize the bed to carry other equipment. Available in four sizes, there's an anti-icer that's perfect for pre-treating parking lots, roads and walkways.

SEE PAGE 22 FOR DETAILED SPECIFICATIONS

QUICK FACTS

VEHICLES:	Pick-ups and Utility Vehicles
TYPE:	Liquid Applicator
CAPACITY:	100, 200, 300 or 400 Gallons
MATERIALS:	Liquid, De-icing Material
CONSTRUCTION:	Corrosion Resistant Polyethylene

Adjustable spray nozzle

Spray boom features 2" or 5 hand adjustable spray nozzles for precise material placement. Each nozzle features 3 different spray patterns.



Easily fits in utility vehicles

The 100 gallon unit fits in most utility vehicles.



* 2 nozzle boom for 100 gallon unit only, all others use 5 nozzle boom.

ANTI-ICERS

www.meyerproducts.com

TAILGATE SPREADERS – BLASTER

BLASTER SPECIFICATIONS

Model	Part #	Hopper Length	Capacity	Weight	Height	Width	Length	Hopper	Operating System	Material	Mounting Method	Vehicle Application
Blaster 350	32000	N/A	350 lbs. 6.5 cu.ft.	175 lbs.	35.5"	49"	24"	Poly	1/2HP 12V Electric	Bagged Rock Salt	2" receiver (std); Cat. 1, 3 point hitch (opt); Flatbed Utility Adapter (opt)	SUV, Light truck, 1/2 ton+
Blaster 350S w/Vibrator	37000	N/A	350 lbs. 6.5 cu.ft.	185 lbs.	35.5"	49"	24"	Poly	1/2HP 12V Electric	Sand	2" receiver (std); Cat. 1, 3 point hitch (opt); Flatbed Utility Adapter (opt)	SUV, Light truck, 1/2 ton+
Blaster 750	33000	N/A	750 lbs. 12.8 cu.ft.	198 lbs. w/o mount	44.5"	49"	24"	Poly	1/2HP 12V Electric	Bagged Rock Salt	Dump, Fixed, Flat Bed (all optional)	1/2 ton+
Blaster 750S w/vibrator	39000	N/A	750 lbs. 12.8 cu.ft.	208 lbs. w/o mount	44.5"	49"	24"	Poly	1/2HP 12V Electric	Sand	Dump, Fixed, Flat Bed (all optional)	1/2 ton+
Blaster 750R	33750	N/A	750 lbs. 12.8 cu.ft.	229 lbs. w/o mount	44.5"	49"	24"	Poly	1/2HP 12V Electric	Bagged 50/50 Rock Salt	Integrated 2" receiver; Hinged (optional)	1/2 ton+
Blaster 750RS	39010	N/A	750 lbs. 12.8 cu.ft.	239 lbs.	44.5"	49"	24"	Poly	1/2HP 12V Electric	Sand	Integrated 2" receiver; Hinged (optional)	1/2 ton+

BLASTER ACCESSORIES

	Blaster 350	Blaster 350S	Blaster 750	Blaster 750S	Blaster 750R	Blaster 750RS
3 Point Hitch Mounting	36500	36500	N/A	N/A	36500	36500
Flatbed Vehicle Mount	35002	35002	35002	35002	N/A	N/A
Fixed Tailgate Mount	N/A	N/A	35200	35200	N/A	N/A
Dump Body Mount	N/A	N/A	35300	35300	N/A	N/A
Flat Bed Tailgate Mount	N/A	N/A	35400	35400	N/A	N/A
Hinged Tailgate Mount	N/A	N/A	N/A	N/A	35160	35160
Sand/Salt Vibrator Kit	34600	Included	34600	Included	34600	Included
Hopper Screen 2" x 2"	34700	34700	34700	34700	34700	34700
Hopper Screen 1/2" x 1/2"	34701	34701	34701	34701	34701	34701
Receiver Hitch Lock 3"	07695	07695	N/A	N/A	07695	07695
Flow Gate Assembly	34900	34900	34900	34900	34900	34900
Industrial Light Kit RD	34609	34609	34609	34609	34609	34609
Industrial Light Kit HD	34610	34610	34610	34610	34610	34610
Universal Motor Guard	36407	36407	36407	36407	36407	36407
Fine Salt Auger Kit*	34118	34118	34118	34118	34118	34118
Chain Auger Kit*	34109	34109	34109	34109	34109	34109
Coarse Material Brush Auger Retrofit Kit**	34300	34300	34300	34300	34300	34300
Fine Material Brush Auger Retrofit Kit**	34301	34301	34301	34301	34301	34301

* Recommended to use with Sander/Vibrator kit 34600

** Brush auger kits 34300 and 34301 are used to retrofit spreaders with 34004 auger. Use 34302 and 34303 as replacement augers for spreaders that shipped with brush auger or 34306 auger as original equipment.

TAILGATE SPREADERS – BL SPREADERS AND MATE™

BL SPREADERS SPECIFICATIONS

Model	Part #	Capacity	Height	Weight	Width	Depth	Hopper	Operating System	Mounting Method	Vehicle Application
BL240	31100	240 lbs.	32"	92 lbs.	25"	21"	Poly	1/6HP 12V Electric	2" receiver hitch mount (std)	Class 1, SUV's, Light Truck, 3/4 or 1 Ton Trucks and Utility Vehicles
BL400	36100	400 lbs.	41"	96 lbs.	25"	21"	Poly	1/6HP 12V Electric	2" receiver hitch mount (std)	Class 1, SUV's, Light Truck, 3/4 or 1 Ton Trucks and Utility Vehicles
BL750	39100	750 lbs.	46"	103 lbs.	36"	26"	Poly	1/6HP 12V Electric	2" receiver hitch mount (std)	Class 1, SUV's, Light Truck, 3/4 or 1 Ton Trucks and Utility Vehicles

MATE™ SPECIFICATIONS

Model	Part #	Capacity	Weight	Height	Width	Depth	Hopper	Operating System	Mounting Method	Vehicle Application
Mate XL	38000	9.0 cu. ft.	216 lbs.	31"	48"	33"	Poly	1/6HP 12V Electric	Tailgate Strap	1/2 ton - 1 ton (2-3 GVW Class)

BL240/400/750 AND MATE™ ACCESSORIES

	BL240/BL400/BL750	Mate™
3 Point Hitch Mounting	36500	38200
Salt Screen	N/A	38260
Tailgate Swing Kit	N/A	35150
Motor Guard	N/A	38250
Spreader Controller	34405	22800
Flow Gate Controller	34900	N/A
Vibrator Kit	34606	N/A
The Big Yellow Box	32403	32403
LED Rear Light Package	34610	N/A
Halogen Rear Light Package	34609	N/A
Receiver Hitch Lock	07695	07695
Meyer Dielectric Grease	15632	15632
Meyer Coolube Grease – Cartridge	15182	15182
Meyer Chain and Cable Lube – Aerosol	15184	15184
Meyer Coolube Grease – Aerosol	15186	15186
Meyer Sno-Flow Industrial Paint – Brush Yellow (4/1 qt. cans/UPS)	08755	08755
Meyer Sno-Flow Industrial Paint – Spray Case Yellow (12 cans/case)	08677	08677
Meyer Sno-Flow Industrial Paint – Spray Case Black (12 cans/case)	08676	08676

INSERT HOPPER SPREADERS – CROSSFIRE AND POLYHAWK

CROSSFIRE SPECIFICATIONS

Model	Part #	Hopper Length	Capacity	Pre-Wet Capacity	Weight	Height	Width	Length	Hopper	Operating System	Mounting Method	Drive System
CF-6 Standard	64740	6 ft.	1.5 cu. yd	N/A	420 lbs.	37"	70"	94"	92"	Dual 1/2HP 12V Electric	Strap	Auger
CF-8 Standard	64742	8 ft.	2.0 cu. yd	N/A	625 lbs.	37"	70"	118"	115"	Dual 1/2HP 12V Electric	Strap	Auger
CF-6 Deluxe	64741	6 ft.	1.5 cu. yd	175 gallons	420 lbs.	37"	70"	94"	92"	Dual 1/2HP 12V Electric	Strap	Auger
CF-8 Deluxe+	64743	8 ft.	2.0 cu. yd	200 gallons	625 lbs.	37'	70"	118'	115'	Dual 1/2HP 12V Electric	Strap	Auger

CROSSFIRE ACCESSORIES

Description	CFS-6	CFS-8	CFD-6	CFD-8
Extended Spinner Chute Assembly	64758	64758	64758	64758
Vibrator Kit	63390	63390	63390	63390
Pre-Wet Kit (For Standard Models)	64759	64759	Included	Included
Side Extension	64762	64763	64762	64763
GPS Ground Speed Control Kit	N/A	N/A	64754	64754
Tarp Kit	64744	64745	64744	64745
Top Screen	64746	64747	64746	64747

POLYHAWK SPECIFICATIONS

Model	Part #	Hopper Length	Capacity	Weight	Height	Width	Length	Hopper	Operating System	Mounting Method Hold Down Kit	Conveyor Type
PolyHawk PV B&S (10.5 HP)	66074	6 ft.	1.5 cu. yd	625 lbs.	35"	50"	90"	72"	10.5HP B&S gas	Part #62562	Drag Chain
PolyHawk PV Honda (11 HP)	66075	6 ft.	1.5 cu. yd	625 lbs.	35"	50"	90"	72"	11HP Honda gas	Part #62562	Drag Chain
PolyHawk PV Electric	66076	6 ft.	1.5 cu. yd	645 lbs.	35"	50"	90"	72"	Dual 1/2HP 12V Electric	Part #62562	Drag Chain
PolyHawk PV Central Hydraulic	66077	6 ft.	1.5 cu. yd	600 lbs.	35"	50"	90"	72"	Central Hydraulics	Part #62562	Drag Chain
PolyHawk PV B&S (10.5 HP)	63898	8 ft.	2.0 cu. yd	850 lbs.	35"	50"	114"	96"	10.5HP B&S gas	Part #62562	Drag Chain
PolyHawk PV Honda (11 HP)	63899	8 ft.	2.0 cu. yd	850 lbs.	35"	50"	114"	96"	11HP Honda gas	Part #62562	Drag Chain
PolyHawk PV Electric	64505	8 ft.	2.0 cu. yd	855 lbs.	35"	50"	114"	96"	Dual 1/2HP 12V Electric	Part #62562	Drag Chain
PolyHawk PV Central Hydraulic	63901	8 ft.	2.0 cu. yd	776 lbs.	35'	50"	114'	96'	Central Hydraulics	Part #62562	Drag Chain

INSERT HOPPER SPREADERS – LPV AND PV

LPV SPECIFICATIONS

Model	Part #	Hopper Length	Capacity	Weight	Height	Width	Length	Hopper	Operating System	Mounting Method Hold Down Kit	Vehicle Application	Conveyor System
LPV- Electric Utility	63394	3 ft.	0.3 cu. yd.	396 lbs.	25"	36"	56"	Stainless Steel	1/2HP 12V Electric	Part #62562	Utility Vehicle	Belt over Chain
LPV- Electric Utility	63395	4 ft.	0.43 cu. yd.	434 lbs.	25"	36"	68"	Stainless Steel	1/2HP 12V Electric	Part #62562	Utility Vehicle	Belt over Chain

LPV ACCESSORIES

	LPV 3 Ft. SS	LPV 4 Ft. SS
6" Side Extension	N/A	N/A
LPV, PV Hold Down Kit	62562	62562
Battery Harness Kit	N/A	N/A

PV SPECIFICATIONS

Model	Part #	Hopper Length	Capacity	Weight	Height	Width	Length	Hopper	Operating System	Mounting Method Hold Down Kit	Vehicle Application	Conveyor System
BL600	64238	6 ft.	1.5 cu. yd.	465 lbs.	34"	50"	93"	Stainless Steel	6.5HP B&S Gas	Part #62562	3/4 ton + (2-3 GVW Class)	Drag Chain
PV-B&S 10.5 HP	63790	7 ft.	1.8 cu. yd.	980 lbs.	34"	50"	102"	Stainless Steel	10.5HP B&S Gas	Part #62562	3/4 ton + (2-3 GVW Class)	Drag Chain
PV-Honda 11.0 HP	63791	7 ft.	1.8 cu. yd.	980 lbs.	34"	50"	102"	Stainless Steel	11.0HP Honda Gas	Part #62562	3/4 ton (2-3 GVW Class)	Drag Chain
PV-B&S 10.5 HP	63792	8 ft.	2.0 cu. yd.	1040 lbs.	34"	50"	114"	Mild Steel	10.5HP B&S Gas	Part #62562	1 ton 2-3 GVW Class)	Drag Chain
PV-B&S 10.5 HP	63794	8 ft.	2.0 cu. yd.	1040 lbs.	34"	50"	114"	Stainless Steel	10.5HP B&S Gas	Part #62562	1 ton (2-3 GVW Class)	Drag Chain
PV-Honda 11.0 HP	63795	8 ft.	2.0 cu. yd.	1040 lbs.	34"	50"	114"	Stainless Steel	11.0HP Honda Gas	Part #62562	1 ton (2-3 GVW Class)	Drag Chain
PV Dual Electric	64448	8 ft.	2.0 cu. yd.	950 lbs.	34"	50"	114"	Stainless Steel	1/2HP Dual Elec Motors	Part #62562	1 ton (2-3 GVW Class)	Drag Chain

PV ACCESSORIES

	PV 7 Ft. SS 10.5HP B&S	PV 7 Ft. SS 11HP Honda	PV 8 Ft. SS 10.5HP B&S	PV 8 Ft. SS 11HP Honda	PV 8 Ft. SS Dual Elec.
LPV, PV Hold Down Kit	62562	62562	62562	62562	62562
LPV, PV Vehicle Wiring Harness	62565	62565	62565	62565	N/A
Wireless Controller Package (Gas)	63688	63688	63688	63688	N/A
PV 6" Side Extensions SS	63925	63925	63926	63926	63926
Vibrator Kit	63390	63390	63390	63390	63390
PV Tarp Kit (1.8 and 2.0 cu. yd.)	62546	62546	62546	62546	62546
30 Gal. PV Pre-Wet System (2-15 gal.)	63938	63938	63938	63938	63938

INSERT HOPPER SPREADERS – MDV

MDV SPECIFICATIONS

Model	Part #	Hopper Length	Capacity	Weight	Height	Width	Length	Hopper	Operating System	Mounting Method Hold Down Kit	Flow Rate	Conveyor Type
MDV-944 B&S-SS	63948	9 ft.	4.0 cu. yd.	1410 lbs.	44"	70"	127"	Stainless Steel	10.5HP B&S Gas	Part #62562	N/A	Drag Chain
MDV-944 Honda-SS	63949	9 ft.	4.0 cu. yd.	1410 lbs.	44"	70"	127"	Stainless Steel	11.0HP Honda Gas	Part #62562	N/A	Drag Chain
MDV-944 Hydraulic-SS	63950	9 ft.	4.0 cu. yd.	1250 lbs.	44"	70"	127"	Stainless Steel	Central Hydraulics	Part #62562	15 GPM @ 1,500 PSI (max)	Drag Chain
MDV-1044 B&S-SS	63954	10 ft.	4.5 cu. yd.	1570 lbs.	44"	70"	139"	Stainless Steel	10.5HP B&S Gas	Part #62562	N/A	Drag Chain
MDV-1044 Honda-SS	63955	10 ft.	4.5 cu. yd.	1570 lbs.	44"	70"	139"	Stainless Steel	11.0HP Honda Gas	Part #62562	N/A	Drag Chain
MDV-1044 Hydraulic-SS	63956	10 ft.	4.5 cu. yd.	1426 lbs.	44"	70"	139"	Stainless Steel	Central Hydraulics	Part #62562	15 GPM @ 1,500 PSI (max)	Drag Chain
MDV-944 Hydraulic Auger	63615	9 ft.	4.0 cu. yd.	1200 lbs.	44"	70"	127"	Stainless Steel	Central Hydraulics	Part #62562	15 GPM @ 1,500 PSI (max)	Auger
MDV-1044 Hydraulic Auger	63619	10 ft.	4.5 cu. yd.	1360 lbs.	44"	70"	139"	Stainless Steel	Central Hydraulics	Part #62562	15 GPM @ 1,500 PSI (max)	Auger
MDV-A 844	64451	8 ft.	3.5 cu. yd.	1160 lbs.	44"	70"	124"	Stainless Steel	12V Electric Auger	Part #62562	N/A	Auger
MDV-A 944	64539	9 ft.	4 cu. yd.	1320 lbs.	44"	70"	136"	Stainless Steel	12V Electric Auger	Part #62562	N/A	Auger
MDV-A 1044	64540	10 ft.	4.5 cu. yd.	1480 lbs.	44"	70"	148"	Stainless Steel	12V Electric Auger	Part #62562	N/A	Auger

MDV ACCESSORIES

	MDV-A844 Auger Elec.	MDV-944 SS 10.5HP B&S	MDV-944 SS 11HP Honda	MDV-944 SS Hydr.	MDV-944 SS Hydr. Auger	MDV-A944 Auger Elec.	MDV-1044 SS 10.5HP B&S	MDV-1044 SS 11HP Honda	MDV-1044 SS Hydr.	MDV-1044 SS Hydr. Auger	MDV-A1044 Auger Elec.
Wireless Controller Package (Gas)	N/A	63688	63688	N/A	N/A	N/A	63688	63688	N/A	N/A	N/A
Chain Oiler	N/A	62126	62126	62126	62126	N/A	62126	62126	62126	N/A	N/A
12" Side Extensions	64578	64128	64128	64128	64128	64580	64130	64130	64130	64130	64582
60 Gal. MDV Pre-Wet System (2-30 gal.)	64131	64131	64131	64131	64131	64131	64131	64131	64131	64131	64131
Vibrator Kit	63390	63390	63390	63390	63390	63390	63390	63390	63390	63390	63390
Tarp Kit	62260	62261	62261	62261	62261	62261	62262	62262	62262	62262	62262

DUMP TRUCK SPREADERS – UTG AND RTG

UTG SPECIFICATIONS

Model	Part #	Hopper Length	Capacity	Weight	Height	Width	Depth	Hopper	Operating System
BL960	64230	N/A	N/A	450 lbs.	19"	96"	18"	Stainless Steel	Hydraulic
BL960 CD	66002	N/A	N/A	450 lbs.	19"	96"	18"	Stainless Steel	Hydraulic
UTG Direct Drive-SS	63546	N/A	N/A	540 lbs.	19"	96"	18"	Stainless Steel	Hydraulic
UTG Gear Drive-SS	63548	N/A	N/A	571 lbs.	19"	96"	18"	Stainless Steel	Hydraulic
UTG CD Electric	63902	N/A	N/A	450 lbs.	19"	96"	18"	Stainless Steel	1/2HP 12V Electric
UTG DD Electric	63903	N/A	N/A	450 lbs.	19"	96"	18"	Stainless Steel	1/2HP 12V Electric

RTG SPECIFICATIONS

Model	Part #	Hopper Length	Capacity	Weight	Height	Width	Fits Bed Width (ID)	Depth	Hopper	Operating System
RTG CD Electric	63907	N/A	N/A	540 lbs.	23"	84"	84" - 90"	16.5"	Stainless Steel	1/2HP 12V Electric

UTG AND RTG ACCESSORIES

	UTG	RTG
Control Valve (Hydraulic Units Only)	62213	62213
Central Hose Kit (Hydraulic Units Only)	62214	62214
Central Pump Kit (Hydraulic Units Only)	61199	61199
Central 7 Gal Tank Kit (Hydraulic Units Only)	61193	61193
135 Gal UTG Pre-Wet System	63921	N/A
Dielectric Grease	15632	15632
Paint Yellow Spray (12/case)	08677	08677
Paint Yellow Cans (4/1qt.)	08755	08755
Paint Black Spray (12/case)	08676	08676

WALK BEHIND BROADCAST SPREADERS – HOTSHOTS

HOTSHOT SPECIFICATIONS

Model	Part #	Capacity	Weight	Handle Height*	Height	Width	Length	Hopper	Frame	Operating System	Spreading Width	Material
Hotshot 85	38115	1.0 cu. ft.	20 lbs.	37.5"	25"	23"	35"	Poly	Carbon	Manual	10 ft.	Sand, Salt, Seed and Any Free Flowing Material
Hotshot 120	38210	1.5 cu. ft.	43 lbs.	39"	30"	30"	40"	Poly	Stainless	Manual	18 ft.	Sand, Salt, Seed and Any Free Flowing Material
Hotshot 70 RD	38170	0.9 cu. ft.	25 lbs.	38"	28"	29"	41"	Poly	Carbon	Manual	12 ft.	Sand, Salt, Seed and Any Free Flowing Material
Hotshot 70 HD	38180	0.9 cu. ft.	36 lbs.	41.5"	26"	28"	48"	Poly	Stainless	Manual	12 ft.	Sand, Salt, Seed and Any Free Flowing Material
Hotshot 100 HD	38160	1.25 cu. ft.	43 lbs.	41.5"	28"	29"	48"	Poly	Stainless	Manual	18 ft.	Sand, Salt, Seed and Any Free Flowing Material

* At level

HOTSHOT ACCESSORIES*

	Hotshot 50	Hotshot 70	Hotshot 70 HD	Hotshot 85	Hotshot 100 HD	Hotshot 120
Weather Cover/Shower Cap	PSB16443	PSB14606	PSB14606	AF40883	PSB14872	AF40825
Salt Deflector Shield	N/A	PSB15464	PSB15972	N/A	PSB16096	AF46119
Internal Top Screen	N/A	PSB14603	PSB14603	N/A	PSB14863	AF47441

* Replacement items/all Hotshots come standard with above accessories

DROP SPREADER - HOTSHOT 50 AND HOTSHOT 100

DROP SPREADER SPECIFICATIONS

Model	Part #	Capacity	Weight	Handle Height*	Height	Width	Depth	Hopper	Operating System	Spreading Width	Material
Hotshot 100 Drop	38191	1.75 cu. ft.	45 lbs.	32.5"	16.5"	49"	44"	Stainless Steel	Manual	35"	Salt, 50/50 Salt/Sand and Sand
Hotshot 50 Drop	38185	.8 cu. ft.	35 lbs.	46"	10"	20"	8"	Poly	Manual	20"	Sand, Salt, Seed and Any Free Flowing Material

* At level

ATV SPREADER

ATV SPREADER SPECIFICATIONS

Model	Part #	Capacity	Weight	Height	Width	Depth	Hopper	Operating System	Mounting Method	Vehicle Application
BL 125	31125	125 lbs.	45 lbs.	36"	29.5"	16.5"	Poly	1/16 HP 12V Electric	Universal	ATV

DUMP TRUCK CROSSOVER CONVEYOR

TAILGATE CROSSOVER CONVEYOR SPECIFICATIONS

Model	Part #	Hopper Length	Capacity	Weight	Height	Width	Depth	Hopper	Operating System	Mounting Method	Vehicle Application
Cross Conveyor-STCC	62729	102"	N/A	1100 lbs.	32"	102"	N/A	Mild Steel	Hydraulic	Under Tailgate	Dump Body (5-6-7 GVW Class)

TAILGATE CROSSOVER CONVEYOR ACCESSORIES

	102" STCC Cross Conveyor
Chain Oiler	62126
Hose Kit Hydr. Spreader	61199
Rear Light Bar Kit	63957
Reversing Valve	63958
Spinner ACY Kit	63959
Four Ft. Motorized Ext.	63960
Conveyor End Extension	64704
Folding Leg Stand	64703
Central Hose Kit (Hydraulic Units Only)	62214
Central Pump Kit (Hydraulic Units Only)	61199
Central 7 Gal Tank Kit (Hydraulic Units Only)	61193
Dielectric Grease	15632
Paint Yellow Spray (12/case)	08677
Meyer Coolube Grease - Cartridge	15182
Meyer Chain and Cable Lube - Aerosol	15184
Meyer Coolube Grease - Aerosol	15186
Paint Yellow Cans (4/1qt.)	08755
Paint Black Spray (12/case)	08676

LIQUID APPLICATION (ANTI-ICERS)

ANTI-ICER SPECIFICATIONS

Model	Tank Capacity	Weight	Height	Width	Depth	Hopper	Drive	Remote Start	Mounting Method	Vehicle Application
100 gal. Tank Only	100 gallons	410 lbs.	35"	66"	39"	Poly	6.5HP Power Pro	Yes	Slide In/Tension Bar	1/2 Ton+
200 gal. Tank Only	200 gallons	440 lbs.	37"	70"	39"	Poly	6.5HP Power Pro	Yes	Slide In/Tension Bar	3/4 Ton+
300 gal. Tank Only	300 gallons	470 lbs.	37"	70"	39"	Poly	6.5HP Power Pro	Yes	Slide In/Tension Bar	1 Ton+
400 gal. Tank Only	400 gallons	500 lbs.	39"	71"	52"	Poly	6.5HP Power Pro	Yes	Slide In/Tension Bar	1 Ton+

ANTI-ICER TANKS AND ACCESSORIES

Description	ITEM #
TANKS: All tanks include standard 6.5HP Subaru Engine, remote control and pump	
100 GALLON TANK	64506
200 GALLON TANK	64507
300 GALLON TANK	64508
400 GALLON TANK	64509
ENGINE UPGRADE: Substitute a 5.5HP Honda engine with electric start	
HONDA 5.5HP ENGINE UPGRADE	64510
HOSE REEL: Note that an 18" Hose reel is required in order to accommodate a 300' hose	
12" MANUAL HOSE REEL	64511
12" ELECTRIC HOSE REEL	64512
18" MANUAL HOSE REEL	64513
18" ELECTRIC HOSE REEL	64514
HOSE	
150 Ft. HOSE	64225
300 Ft. HOSE	64226
GUN	
STANDARD GUN KIT	64515
BOOM	
2 NOZZLE BOOM (USE WITH 100 GAL ONLY)	64542
5 PORT BOOM (USE WITH 200-400 GAL)	64543
OPTIONAL ACCESSORIES	
BLASTER/ANTI-ICER COMBO KIT: includes: Hose Barb, Hose, Nozzle Bracket, Nozzle Body and Boom Bracket	64516
DO ALL GUN	64224
ROOT FEEDER	64517
TREE GUN	64518
LITE-TREE GUN	64519
TERMITE TOOL	64520
TANK FILTER	64521
MEASURING WHEEL	64522
CARGO BAR	64223
PRESSURE GAUGE	64523



REINVENTED EVERY DAY.

DISTRIBUTED BY:

Meyer Products LLC
18513 Euclid Ave., Cleveland, Ohio 44112
Phone: 216-486-1313
Fax: 216-486-1321
www.meyerproducts.com

Meyer Spreaders are protected by one or more of the following patents: 6698997, CA 2,415,540 C, 7588195, 8448882, 8505837, 8523086, 8657208, 6186731, 6,793,154 B2, 6722590, 6715703, 6978952, 6932287, 8505838, 8827002, 5842649, CA 2,435,106 C, 6364598, 9,127,425, 9,127,425, 9,371,621, 6,722,590, 6,715,703, 6,932,287, 6,978,252, 9,371,621, 9,085,862, 9,096,979.