



# Self-Contained Debris Collector

## DCL800SM

Kubota WG3800-G-E3  
4-cylinder Gasoline  
engine rated at 87HP.

- 28” suction impeller
- 16” dia. x 144” long urethane suction hose
- 3-Axis hose boom with in-cab controls

The DCL800SM has the best suction of any unit in it’s class.  
Contact ODB to order yours today!

### DCL800SM



Sourcewell  
Awarded Contract  
Contract # 031121-ODB



\*Specifications subject to change at any time without notice.

\*Standard color is white.

\*Units shown with options.



800.476.2434  
ciequipment.com

4315 Taggart Creek Road  
Charlotte, NC 28208



# DCL800SM

## Automated Debris Collection Loader-Chassis Mounted



### Specifications

#### Engine - Gas

Kubota WSG3800 3.8L 4-cylinder gasoline engine, rated at 87HP, meets EPA T2 & CARB T3 standards.

#### Engine Controls

Electronic engine controls with safety shut down.

#### Drive

Belt driven via a 4-groove power band.

#### Hoist

Gear driven hydraulic pump powers underbody hoist that dumps to 52 degrees.

#### Hopper

Container constructed of 12 gauge steel with vented top and top hinged rear door. Available in 14, 20, 25 & 30 cu.yd. capacities.

#### Truck Body

Freightliner M2-106 chassis with dual steering.

#### Fuel Tank

40-gallon polyethylene fuel tank.

#### Options

- Eco Mode
- Fluid drive coupler in lieu of standard clutch
- Bottom Exhaust for hopper
- Air scoop to direct exhausted air to the rear
- Perforated top screens with 3/16" holes
- Urethane coated liners for blower housing
- Rotary self-cleaning air screen for radiator
- Urethane suction hose in lieu of rubber
- Driver's side (street) pick up
- Chipper door with trailer hitch package
- Two (2) surface mounted LED flashers
- LED Traffic directional light bar on rear

#### Engine - Option

John Deere 4045TFC03 4-cylinder diesel engine rated at 74HP - Final T4

#### Radiator Screen

Boxed corrugated radiator screen constructed from perforated steel to increase air flow for better cooling.

#### PTO

13" clutch assembly with 2.25" PTO shaft and safety engagement system.

#### Throttle

Remote electric throttle and clutch engagement.

#### Hose Boom

3-Axis hose boom powered by electric/hydraulic pump with proportional in-cab controls.

#### Hose

16" x 144" urethane intake hose with steel nozzle.

#### Impeller

28" diameter suction impeller with six 3/8" thick T-1 steel blades. Replaceable 1/4" thick abrasion resistant steel liners.

#### Camera

Rear backup camera with 5.6" color screen.

#### Lights

LED type DOT trailer lights. Two amber LED flashers in the rear.

#### Paint

All components are pre-painted with PPG paint. Hopper - standard white, other custom paint colors available as options.