



Self-Contained Debris Collector

DCL800TM

Kubota WG3800-G-E3
4-cylinder Gasoline
engine rated at 87HP.

- 28” suction impeller
- 16” dia. x 120” long rubber suction hose
- Tandem rubber Torflex axles

The DCL800TM
has the best suction of
any unit in it’s class.
Contact ODB
to order yours today!



*Specifications subject to change
at any time without notice.

DCL800TM



*Standard color is white.

*Units may be shown with options.



800.476.2434
ciequipment.com

4315 Taggart Creek Road
Charlotte, NC 28208



DCL800TM

Debris Collection Loader-Trailer Mounted



Specifications

Engine - Gas

Kubota WG3800 3.8L 4-cylinder gasoline engine, rated at 87HP, meets EPA T2 & CARB T3 standards.

Engine Controls

Electronic engine controls with safety shut down.

Drive

Belt driven via a 4-groove power band.

Hoist

Gear driven hydraulic pump powers underbody hoist that dumps to 52 degrees.

Hopper

Container constructed of 12 gauge steel with vented top and side hinge rear doors. Available in 14, 20, 25 & 30 cu.yd. capacities.

Axles

14CY - Dual 3.5" Torflex axles rated at 16,000 lbs.
20CY - Dual 5" Torflex axles rated at 20,000 lbs.
25/30CY-Dual 5" Torflex axles rated at 24,000 lbs.
Equipped w/ electric brakes with break-away actuator.

Tires

14CY - (4) ST235-85R16 radial tires on steel wheels.
20/25/30CY - (8) 235/80R16E tires on steel wheels.

Options

- Eco Mode
- 3-axis hose boom (up/dn, left/rt, in/out)
- Hydraulic parking jack in lieu of manual
- Fluid drive coupler in lieu of standard clutch
- Remote electric throttle for engine
- Urethane suction hose in lieu of rubber
- Urethane coated liners for blower housing
- Driver's side (street) pick up
- Perforated top screens with 3/16" holes
- Air Scoop or Bottom Exhaust on box

Engine - Option

John Deere 4045TFC03 4-cylinder diesel engine rated at 74HP - Final T4

Radiator Screen

Boxed corrugated radiator screen constructed from perforated steel to increase air flow for better cooling.

PTO

13" clutch assembly with 2.25" PTO shaft and safety engagement system.

Hose Boom

Hydraulic hose boom powered by 12v electric / hydraulic pump.

Hose

16" x 100" rubber suction hose with steel nozzle.

Impeller

28" diameter suction impeller with six 3/8" thick T-1 steel blades. Replaceable 1/4" thick abrasion resistant steel liners.

Fuel Tank

40-gallon polyethylene fuel tank.

Pintle Eye

Heavy-duty height adjustable pintle eye with three quick release pins requiring no tools.

Parking Jack

Manual parking jack with drop foot.

Lights

LED type DOT trailer lights. Two amber LED flashers in the rear.

Paint

All components are pre-painted with PPG paint - Hopper - standard white, other custom paint colors available as options.