



Self-Contained Debris Collector

DCL8031

Kubota D902
24HP liquid-cooled,
3-cylinder diesel
engine, Final T4.

- 10 cubic yard hopper
- 12" dia. x 120" long urethane hose
- Tandem rubber Torflex axles

DCL8027

Kawasaki FD750D 27HP
liquid-cooled, 4-stroke
OHV V-twin cylinder
gasoline engine.

DCL8031



DCL8027



Sourcewell
Awarded Contract
Contract # 031121-ODB



*Specifications subject to change at any time without notice.

*Standard color is white.

*Units may be shown with options.



800.476.2434
ciequipment.com

4315 Taggart Creek Road
Charlotte, NC 28208



DCL8031 or DCL8027

Debris Collection Loader-Trailer Mounted



Specifications

Engine - 8031

Kubota D902 liquid-cooled, 3-cylinder diesel engine, 24HP, Final T4.

Engine Controls

Full display shows engine temperature, RPM, oil pressure, battery volts, fuel level and engine hours. Full throttle control and fault code displays are also included.

Hoist

Hopper has an underbody hydraulic dumping hoist that tips to 52 degrees. Electric / hydraulic pump powers the hoist.

Axles

Tandem rubber Torflex axles with a combined 12,000 pound rating. Four ST225-75-R15 radial tires mounted on white spoke wheels. Electric brakes with break-away actuator.

Hose Boom

Manual swing overhead boom assembly.

Hose

12" diameter x 120" urethane suction hose with steel nozzle is stored to the front of the unit.

Lights

LED type DOT trailer lights.

Options

- Hydraulic boom in lieu of manual boom
- Litter kit including additional 10' x 8" hose with 4' long aluminum nozzle
- Also available in hook lift version

Engine - 8027

Kawasaki FD750D liquid-cooled, 4-stroke OHV V-twin cylinder gasoline engine, 27HP.

Radiator

Pressurized, heavy duty. Trash style with 6-blade fan.

Drive

Belt drive via a 3-groove power band.

PTO

Manual slide to engage / disengage the vacuum system.

Fuel Tank

12-gallon cross-link polyethylene fuel tank.

Hopper

10 cubic yd. with dual side hinged rear doors for easy access to the hopper for dumping. Top of hopper is equipped with two easily removeable exhaust screens.

Impeller

20" diameter suction impeller with six 3/8" thick steel blades. Replaceable 1/4" thick abrasion resistant steel liners.

Pintle Eye

Heavy-duty height adjustable pintle eye with three quick release pins requiring no tools.

Parking Jack

Manual parking jack with drop foot.

Paint

All components are pre-painted with PPG paint - Hopper - standard white color only.