



Tow-Behind Debris Collector

LCT600

Kubota WG3800-G-E3
4-cylinder Gasoline
engine rated at 87HP.

- 28" suction impeller
- 16" dia. x 120" long rubber suction hose
- Hydraulic hose boom

The LCT600 has the best suction of any unit in it's class. Contact ODB to order yours today!



*Specifications subject to change at any time without notice.



*Standard color is white.

*Units may be shown with options.



800.476.2434
cieequipment.com

4315 Taggart Creek Road
Charlotte, NC 28208



LCT600

Tow-Behind Debris Collector-Trailer Mounted



Specifications

Engine - Gas

Kubota WSG3800 3.8L 4-cylinder gasoline engine, rated at 87HP, meets EPA T2 & CARB T3 standards.

Engine Controls

Electronic engine controls with safety shut down.

Drive

Belt driven via a 4-groove Kevlar power band.

PTO

13" clutch assembly with 2.25" PTO shaft and safety engagement system.

Trailer

1/4" thick trailer deck with channel members on the ends.

Axles

Single 6,000 lb. Torflex axle with EZ lube hubs. Equipped w/ electric brakes with break-away actuator.

Tires

(2) ST225-75-R15 radial tires on steel wheels

Options

- Eco Mode
- 2 or 3-axis hose boom (up/dn, left/rt, in/out)
- Wireless boom controls (multi-axis boom only)
- Hydraulic parking jack in lieu of manual
- Fluid drive coupler in lieu of standard clutch
- Remote electric throttle for engine
- Remote electric clutch for engine
- 45 degree intake hose flange
- Urethane suction hose in lieu of rubber
- Urethane coated liners for blower housing
- Driver's side (street) pick up
- 38" Hydraulic curb nozzle
- Hydraulic agitator for curb nozzle

Engine - Option

John Deere 4045TFC03 4-cylinder diesel engine rated at 74HP - Final T4

Radiator Screen

Boxed corrugated radiator screen constructed from perforated steel to increase air flow for better cooling.

Hose Boom

Hydraulic hose boom powered by 12v electric / hydraulic pump.

Intake Hose

16" x 120" rubber suction hose with steel nozzle.

Impeller

28" diameter suction impeller with six 3/8" thick T-1 steel blades. Replaceable 1/4" thick abrasion resistant steel liners.

Exhaust Hose

16" diameter x 48" long rubber exhaust hose

Fuel Tank

44-gallon polyethylene fuel tank.

Pintle Eye

Heavy-duty height adjustable pintle eye with three quick release pins requiring no tools.

Parking Jack

Manual parking jack with 5" swivel castor wheel.

Lights

LED type DOT trailer lights. One amber LED flasher light at the rear.

Paint

All components are pre-painted with PPG paint - Unit - standard white, Engine - Battleship grey. Other custom paint colors available as options.