



HOME

ABOUT US

PRODUCTS

FINANCING

CONTACT US

A close-up photograph of a snowplow blade in operation. The blade is yellow and black, pushing a pile of snow to the side of a road. The background shows a snowy landscape with trees and a building.

RV SERIES SNOWPLOWS



RV Series Snowplows

The Valk RV Series of snow plows has been in dependable service for over 50 years. Available in manual angle, power angle locking, and double acting reversing cylinders. Tripping options include the standard trip cylinder, exposed compression trip, exposed extension trip, and trip cutting edge designs.

STANDARD FEATURES

- 10 gauge steel moldboard
- 3/16" Moldboard available
- 1/2" Bottom angle & semi-circle assembly
- 5/8" Bottom angle & semi-circle available
- Lengths available: 8', 9', 10', 11', & 12'
- Heights available: 30", 36", & 42"
- Circle widths available: 60", 75" & 116"



POWER REVERSE - LOCKING

Pictured with Built-In Snow Shield, 116" Semi-Circle, cannon style trip cylinder and 8" Caster wheels

← **POWER REVERSE – LOCKING**

Equipped with a mechanical locking block the this power reversing option will hold the plow at the desired angle relieving the cylinders from any plowing forces. Adjustable from 0 degrees to 37 degrees left or right. This option requires open center hydraulics.



DAPR SERIES POWER REVERSE

Pictured with Built-In Snow Shield, 116" Semi-Circle, exposed compression trip assembly and no Caster Assy.

← **DAPR SERIES POWER REVERSE**

For those who do not desire the locking style plow, this plow is equipped with two 3" x 10" double acting reversing cylinders and a cushion valve for cylinder protection. Adjustable from 0 degrees to 37 degrees left or right.

OPTIONS

- Rubber snow shield
- 3/4"x 6" Carbide blade with 1/2"x 6" cover blade
- Rubber cutting edge
- Adjustable skid shoes or mushroom shoes
- Adjustable caster wheel assemblies
- Mouse ear discharge – single or double
- HD Suffix: Heavy duty version – 5/8" bottom angle and semi circle assembly – adds approx 100 to 140 lbs to weight of plow 10 gauge steel moldboard
- 3/16" Moldboard available
- 1/2" Bottom angle & semi-circle assembly
- 5/8" Bottom angle & semi-circle available
- Lengths available: 8', 9', 10', 11', & 12'
- Heights available: 30", 36", & 42"
- Circle widths available: 60", 75" & 116"

— RV SERIES VERSATILITY —

Listed below are some of our more popular model numbers. Please note however, not all model numbers are listed.

Model	Length	Height	Cutting Path At 35°	Approx Weight
RV101-60PR	10'	30"	8' 2"	1350 LBS
RV101-75PR	10'	30"	8' 2"	1390 LBS
RV101-116PR	10'	30"	8' 2"	1490 LBS
RV102-60PR	10'	36"	8' 2"	1550 LBS
RV102-75PR	10'	36"	8' 2"	1590 LBS
RV102-116PR	10'	36"	8' 2"	1650 LBS
RV103-75PR	10'	42"	8' 2"	1660 LBS
RV103-116PR	10'	42"	8' 2"	1760 LBS
RV111-75PR	11'	30"	9' 0"	1580 LBS
RV111-116PR	11'	30"	9' 0"	1680 LBS
RV112-75PR	11'	36"	9' 0"	1680 LBS
RV112-116PR	11'	36"	9' 0"	1680 LBS
RV113-75PR	11'	42"	9' 0"	1780 LBS
RV113-116PR	11'	42"	9' 0"	1730 LBS

Model	Length	Height	Cutting Path At 35°	Approx Weight
RV121-75PR	12'	30"	9' 10"	1830 LBS
RV121-116PR	12'	30"	9' 10"	1750 LBS
RV122-75PR	12'	36"	9' 10"	1850 LBS
RV122-116PR	12'	36"	9' 10"	1800 LBS
RV123-75PR	12'	42"	9' 10"	1900 LBS
RV123-116PR	12'	42"	9' 10"	1950 LBS

POWER REVERSING OPTIONS

- PR Suffix – Power Reverse Locking
- DAPR Suffix – Double Acting Power reverse
- Uses 3" x 10" double acting cylinders 2" rod

SAFETY TRIP OPTION

- No Suffix – Standard Cannon Style Trip Cylinder
- ECT Suffix – Exposed Compression Trip Assembly
- EET Suffix – Exposed Extension Trip Assembly
- TE Suffix – Trip Edge, Enclosed vertically Mounted canisters