



CUSHMAN®

SHUTTLE™ 4



MOVE PEOPLE AND GEAR WITH EASE.

Specifically designed to multi-task, the Shuttle™ 4 combines four-forward facing seats and a spacious cargo bed, ready to transport people and equipment from every corner of your facility. Available with the 13.5 hp EFI gas engine the Shuttle 4 has plenty of power and range to tackle your most demanding days.

**13.5HP
EFI GAS**

**1200LB
TOTAL LOAD
CAPACITY**



CUSHMAN® SHUTTLE™ 4



HEADLIGHTS



BENCH SEATING

RACK-AND-PINION
STEERING

OPTIONS & ACCESSORIES

- Rearview Mirror
- Windshield
- Canopy
- Hour Meter
- Individual Key Switch
- Pinstripes
- Body Color (Forest Green, White or Custom Options)
- On Board Charger
- Turn Signal with Four-Way Flashers
- Brakelights
- LED Headlights
- CE Kit (gas only)
- Wheel Covers
- Limited Slip Differential
- Trail Tires

EFI GAS MODEL

BODY & CHASSIS	
FRAME	Welded Steel w/ DuraShield™ Powder Coat
BODY & FINISH	Injection Molded TPO
STANDARD COLOR	Patriot Blue
DIMENSIONS	
OVERALL LENGTH	133.5 in (339 cm)
OVERALL WIDTH	48.5 in (123 cm)
OVERALL HEIGHT	48.6 in (123 cm) (w/o Roof) / 72.0 in (183 cm) (w/ Struts & Roof)
WHEEL BASE	93.5 in (237 cm)
WHEEL TRACK	34.2 in (87 cm) Front / 38.0 in (97 cm) Rear
GROUND CLEARANCE	4.3 in (11 cm)
CARGO DECK CAPACITY	9 cu ft (.25 m³)
CARGO DECK MATERIAL	Wood Stake Sides
POWER	
POWER SOURCE	4-Cycle, 24.5 ci (401cc)
VALVE TRAIN	Single Cylinder OHV
HORSEPOWER (KW)	13.5 hp (10.1 kW)
ELECTRICAL SYSTEM	Starter/Generator. Solid State Reg.
BATTERY (QTY/TYPE)	One, 12V Maintenance Free
KEY OR PEDAL START	Pedal
AIR CLEANER	Replacable Industrial Rated Dry Cartridge
LUBRICATION	Pressurized Oil System
OIL FILTER	Spin-On
COOLING SYSTEM	Air Cooled
FUEL CAPACITY	5.96 Gallon (22.6 L) Tank
SPEED CONTROLLER	N/A
DRIVE TRAIN	Continuously Variable Transmission
TRANSAXLE	Differential w/ Helical Gears
GEAR SELECTION	Forward - Reverse
REAR AXLE RATIO	11.47:1 (Forward) 14.35:1 (Reverse)
PERFORMANCE	
SEATING CAPACITY	4-Person
WEIGHT W/O BATTERIES	896 lb (406 kg)
CURB WEIGHT	936 lb (425 kg)
VEHICLE LOAD CAPACITY	1200 lb (544 kg)
BED LOAD CAPACITY	400 lb (181 kg)
OUTSIDE CLEARANCE CIRCLE	25.5 ft (7.8 m)
SPEED	14 mph ± 0.5 mph (22.5 kph ± 0.8 kph)
STEERING & SUSPENSION	
STEERING	Self-Compensating Rack & Pinion
SUSPENSION	Leaf Springs w/ Hydraulic Shock Absorbers
SERVICE BRAKE	Rear Wheel Mechanical, Self-Adjusting Drum
PARKING BRAKE	Self-Compensating, Single-Point Engagement
TIRES (FRONT & REAR)	18 x 8.50 - 8 (4 Ply Rated)

www.cushman.com

©2022 Textron Specialized Vehicles Inc.
Features and specifications of the vehicles are subject to change without notice.
Vehicle as photographed may include options not included on base model.

82283-G9 (Rev. 01/2022)



CUSHMAN®

SHUTTLE™ 4 ELITE™



AN INDUSTRY LEADER IN EFFICIENCY.

The Cushman® Shuttle™ 4 is now equipped with the Samsung SDI ELiTE Lithium batteries giving you the highest level of performance and efficiency around your facility. With a spacious cargo bed and four forward facing seats the Shuttle 4 is essential for day-in and day-out operations.

ELiTE
LITHIUM

**MAINTENANCE
FREE BATTERIES**

**SAMSUNG SDI
TECHNOLOGY**

**5-YEAR
BATTERY WARRANTY**

**1200LB
TOTAL LOAD CAPACITY**



CUSHMAN® SHUTTLE™ 4 ELITE™



FOUR, FORWARD FACING SEATS



CARGO BED

RACK-AND-PINION
STEERING

OPTIONS & ACCESSORIES

- Rearview Mirror
- Windshield
- Canopy
- Hour Meter
- Individual Key Switch
- Body Color (Forest Green, White or Custom Options)
- Elite World Charger
- Turn Signal with Four-Way Flashers
- Brake lights
- LED Headlights
- CE Kit (Include Seat Lock)
- Wheel Covers
- Limited Slip Differential

BODY & CHASSIS

FRAME	Welded Steel w/ DuraShield™ Powder Coat
BODY & FINISH	Injection Molded TPO
STANDARD COLOR	Patriot Blue

DIMENSIONS

OVERALL LENGTH	134 in (343 cm)
OVERALL WIDTH	48.5 in (123 cm)
OVERALL HEIGHT	48.6 in (123 cm) (w/o Roof) / 72.0 in (183 cm) (w/ Struts & Roof)
WHEEL BASE	93.5 in (237 cm)
WHEEL TRACK	34.2 in (87 cm) Front / 38.0 in (97 cm) Rear
GROUND CLEARANCE	3.9 in (9.8 cm)
CARGO DECK CAPACITY	9 cu ft (.25 m³)
CARGO DECK MATERIAL	Wood Stake Sides

POWER

POWER SOURCE	56V AC
HORSEPOWER (KW)	14.9 HP (11.1 kW)
ELECTRICAL SYSTEM	48V primary 12V aux.
BATTERY (QTY/TYPER)	56.7V Li-Ion Composite Module + Cell Model
BATTERY CHARGER	56.7V, 811W World Charger, 3M Charging Cord
KEY OR PEDAL START	Pedal
SPEED CONTROLLER	350Amp AC
DRIVE TRAIN	Motor Shaft Direct Drive
TRANSAXLE	Differential w/ Helical Gears
GEAR SELECTION	Dash-Mounted Forward-Neutral-Reverse / Key Switch
REAR AXLE RATIO	16.99:1

PERFORMANCE

SEATING CAPACITY	4-Person
WEIGHT W/O BATTERIES	907 lb
CURB WEIGHT	988 lb
VEHICLE LOAD CAPACITY	1200 lb (544 kg)
BED LOAD CAPACITY	400 lb (181 kg)
OUTSIDE CLEARANCE CIRCLE	25.5 ft (7.8 m)
SPEED	14.9 mph ± 0.5 mph (24.0 kph ± 0.8 kph) (High Speed) 12 mph ± 0.5 mph (19.3 kph ± 0.8 kph) (Low Speed) 16.5 mph

STEERING & SUSPENSION

STEERING	Self-Compensating Rack & Pinion
SUSPENSION	Leaf Springs w/ Hydraulic Shock Absorbers
SERVICE BRAKE	Dual Rear Wheel Mechanical, Self-Adjusting Drum
PARKING BRAKE	Self-Compensating, Single-Point Engagement
TIRES (FRONT & REAR)	18 x 8.50 - 8 (4 Ply Rated)

www.cushman.com

©2022 Textron Specialized Vehicles Inc.
Features and specifications of the vehicles are subject to change without notice.
Vehicle as photographed may include options not included on base model.

82306-G2 (Rev. 01/2022)