

**MODEL: TITAN XD (4 PASSENGER)** 

TYPE: ELECTRIC 48 VOLT INDUSTRIAL BURDEN CARRIER

**MODEL YEAR: 2019** 

Part No:. 671549



Four wheel hydraulic brakes with Intellibrake

• E and EE type rating available

## **PRODUCT SPECIFICATION**

## **CONFIGURATION HIGHLIGHTS**

- Solid state continuously variable AC speed controller for increased efficiency
  Fold down rear seat for added cargo or passengers
- Dash mounted multi-function display for SOC, speed, and hour meter
- 15.3 ft<sup>2</sup> of weather proof cargo deck, easily removable for service

Battery Charger: 1000 Watt, 48VDC, 120/240 VAC 60/50 Hz. UL Listed

Motor: 48 Volt AC induction, solid copper windings. Non vented 16.8 hp (12.5 kW) (Peak)

**Drive Train:** Direct motor shaft connected to transaxle pinion shaft

Electrical System: 48 Volt DC, eight, 6 volt deep cycle batteries (115 minute minimum @ 75 amps, 225 amp-hour @ 20 hr. discharge rate)

**Transaxle:** Differential with helical gears

Brakes: Front hydraulic disc brakes. Rear wheel hydraulic 160mm self-adjusting drum brakes. Intellibrake automatic parking brake

Cargo Bed: Weather proof deck board, 75 in x 41 in (191 x 105 cm). Removable for access to powertrain.

Capacity: Seating for 4 persons, 3000 pound vehicle capacity

## PRODUCT OVERVIEW

PRODUCT OVERVIEW							
Dimensions		Performance					
Overall Length	114.0 in (290 cm)	Capacity	4 Persons				
Overall Width	44.5 in (113 cm)	Dry Weight	1225.0 lb (560 kg) (Without Batteries)				
Overall Height (Steering Wh	eel) 47.5 in (120.6 cm)	Curb Weight	1720.0 lb (780 kg)				
Overall Height (Optional Cal	o) 72.0 in (183 cm)	Cargo Deck Load Capacity	2200 lb (998 kg)				
Wheel Base	67 in (170 cm)	Vehicle load capacity	3000 lb (1361 kg)				
Front Wheel Track	38 in (96.5 cm)	Outside Clearance Circle	21.25 ft (6.47 m)				
Rear Wheel Track	38 in (96.5 cm)	Intersecting Aisle Clearance	84.0 in (213 cm)				
Gnd Clearance @ Differentia	al 4.75 in (12.1 cm)	Speed (Level Ground)	Haul Mode: 14 mph ±.5 (21 kph ± 0.8)				
Cargo Deck Width	41.5 in (105 cm)		Tow Mode: 5 mph $\pm$ .5 (8.1 kph $\pm$ .8)				
Cargo Deck Length	53.5 in (136 cm)	Drawbar	211 lb (96 kg) Normal, 1015 lb (460 kg) Max				
Cargo Deck Load Height	29.0 in (74 cm)	Towing Capacity*	8000 lb (3628 kg)				
Cargo Deck Material	Weather proof deck board	Steering & Suspension					
Vehicle Power		Steering	Rack and Pinion				
Power Source	18 Volts DC	Front Suspension	Independent, Transverse Leaf Spring, Shocks				
Motor Type	AC Induction	Rear Suspension	Leaf Springs & Shock Absorbers				
Horsepower (kW)	6.8 HP (12.5 kW) Peak	Service Brake	Front hydraulic disc, Rear hydraulic drum				
Electrical System	48 Volt	Parking Brake	Intellibrake Automatic Parking Brake				
Batteries (Qty, Type)	Eight, 6 Volt Deep Cycle	Front Tire	5.70 x 8 (Load Range C)				
Key or Pedal Start	Pedal Start	Rear Tires	5.70 x 8 (Load Range C)				
Battery Charger	18V On-Board, 120/240 VAC UL	Body & Chassis					
Speed Controller	150 Amp AC	Frame & Body	Welded steel with DuraShield™ powder coat				
Drive Train	Motor Shaft Direct Drive	Body & Finish	Diamond plate ptn. Polyester primer + acrylic				
Transaxle [	Differential with Helical Gears	Standard Color	Yellow				
Gear Selection	Dash Mounted Forward-Neutral-Reverse	Noise & Vibration	Noise & Vibration				
Rear Axle Ratio			sure; continued A-weighted =/< 70 db(A)				
			S value of weighted acceleration is less than 2.5 m/s <sup>2</sup>				
		Vibration, HAV Highest RM	S value of weighted acceleration is less than 2.5 m/s <sup>2</sup>				
Measurement methods were applied per the ISO 2631 and ISO 534							

standards under conditons of typical vehicle surfaces.



OPTIONS & FIELD INSTALLED ACCESSORIES (Installation not included)*									
Item	Std Opt Fld	Item	Std	Opt	Fld				
TIRES & WHEELS:		ELECTRICAL:			П				
Front & Rear:		Batteries							
5.70 x 8 (Load Range C)	•	T-105 Batteries	•						
5.70 x 8 Solid		T-145 Batteries		•					
5.70 x 8 Non-Marking Solid		Battery Fill System		•					
COLORS:		Battery Chargers							
Vehicle Color - Safety Yellow	•	48V On-Board, 1000 Watt	•						
Vehicle Color - Hunter Green		48V On Board, 1500 Watt		•					
Vehicle Color - Artic White	•	NEMA 5-15P Cord	•						
Vehicle Color - Flame Red	•	NEMA 6-15P Cord		•					
Custom Vehicle Color		Lighting Package:							
WEATHER PROTECTION		LED Brake Lights/Tail Lights	•						
Sun Canopy - Short	•	Headlights	•						
Sun Canopy - Long	•	LED Headlights		•					
Windshield (Requires Long Sun Canopy)	•	Turn Signals		•					
Windshield, Fold Down (Requires Short Sun Canopy)		Miscellaneous:							
Weather Protection Enclosure (Lg Top & Windshld Reqd)	•	Hour Meter	•						
Black Cab with Clear Doors		Operator Presence Switch	•						
CARGO AREA		State of Charge Meter	•						
Box Sides & Tailgate		USB Outlet	•						
Cargo Deck (Steel)		Forward Motion Indicator		•					
GUARDS AND TOWING		Type 'E' Classification		•					
Bumper - Front		Type 'EE' Classification		•					
Bumper - Rear		CE Certification		•					
Hitch, Pintle (Requires Rear Bumper)		Deck Lock		•					
Hitch, Clevis (Requires Rear Bumper)		Hand Brake		•					